

## technical data sheet






EN

### Product specifications

Multi-Ply Oak wood flooring	EN 13489 (Free Class)	DOP PQ2022-9
Dimensions	Plank	600-1900 x 150 x 10/ 3 mm
	Box	10 planks / 2,85 m <sup>2</sup> / 20 kg
	Nested lengths	Max. 2 (min. 600 mm)
	Pallet	54 boxes / 153.90 m <sup>2</sup> / 1080 kg
Density	EN ISO 23996	+/- 650 kg/m <sup>3</sup>
Installation	ISO 24334	T&G (glued)
Top layer		3 mm European oak (Quercus Robur)
Grading		Rustic AB+
Surface		Medium brushed
Bevel		Bevel 4V
Gloss level	60°	5-10%
Finishing		Matt lacquer
Warranty conditions	Residential use	20 years
	Commercial use	upon request
Application	EN 13489	Class 23



### Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-s1 (CWFT)
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m <sup>3</sup>	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m <sup>2</sup> K/W	R = 0.06 m <sup>2</sup> K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: [www.lamett.eu](http://www.lamett.eu)



Rustic AB+

EN

## Grading description

Texture	Medium geborsteld
Grading	Rustiek
Colour variation	Hoog
Sound knots	Toegelaten (<50 mm)
Unsound knots	Toegelaten (<30 mm)
Bark	Niet toegelaten
Sapwood	L < 300mm, B < 20 mm
End crack	Toegelaten
Surface crack	Toegelaten
Insect hole	Niet toegelaten
Decay	Niet toegelaten
Blue/yellow stain	Beperkt toegelaten
Sound heart	Toegelaten
Machine marks	Niet toegelaten



This picture is an indication of the grading as described.

## Grading description — 2 criteria

### Knots

Scale from (rigid) parquet without knots up to planks with more and larger knots



### Colour variation

Scale from (rigid) parquet without knots up to planks with more and larger knots

