

technical data sheet






EN

Grading description

Multi-Ply Oak wood flooring	EN 14342 (Free Class)	DOP PQ2021-2
Dimensions	Plank	650-1900 x 190 x 14/ 3 mm
	Box	6 planks / 2,166 m ² / 16,00 kg
	Nested lengths	5 full planks
	Pallet	55 boxes / 119,13 m ² / 910 kg
Density	EN ISO 23996	+/- 650 kg/m ³
Installation	ISO 24334	Drop Lock (floating or glued)
Top layer		3 mm Asian oak (Quercus Mongolica)
Grading		Rustic B
Surface		Brushed
Bevel		Bevel 4V
Gloss level	60°	10-15%
Finishing		Matt lacquer
Warranty conditions	Residential use	20 years
	Commercial use	upon request
Application	EN 14342	Class 23



Product properties

Property	Test method	min. req.	result
Indoor air certifications			A, REACH
Fire resistance	 EN 13501-1		Dfl-S1
Slip resistance	 EN 13893		DS (≥ 0.30)
Formaldehyde emission	 EN 717-1	≤ 0.124 mg/m ³	E1
Pentachlorofenol content	 EN 12673	< 5 ppm	< detectable limit
Underfloor heating	 EN 12667	R < 0.15 m ² K/W	R = 0,10 m ² K/W OK (max +28°C) + glued
Biological durability			Class 1

Cleaning and maintenance instructions: www.lamett.eu

